

TECHNICAL DATA SHEET

DECALCIT FILTER

FILTER DESCALER

Removes limescale deposits accumulated in the filter



CLEANERS

ADVANTAGES

- **High-performance granules**
- **Suitable for all types of filters, including cartridge filters**
- **Fast-acting**
- **Phosphate-free**
- **Effective limescale removal**
- **Long-lasting protection**

PRODUCT FUNCTION

Filter maintenance

Decalcit Filter consists of highly effective granules that quickly remove limescale from all types of filters. Regular use optimises filter performance and enhances the effectiveness of water treatment products.

PRODUCT DESCRIPTION

Fast-dissolving granules.

Compatible with all treatment methods (chlorine, bromine, active oxygen, etc.) and all filtration systems (diatomaceous earth, cartridges, sand, glass.).

Contains: non-ionic surfactants (<5 %)

Available size: 1 kg

DOSING INFORMATION

Filter type: All	Where: In the skimmer
Water volume: All	When: If necessary

APPLICATION

Sand filter:

- Carry out a thorough backwash. At the start and end of the season, dissolve 1 kg DECALCIT FILTER in 10 L of water in a bucket, pour the solution in the open filter container and let it work overnight.
- Turn the filter back on and carry out another thorough backwash of at least 3 – 5 minutes.

Cartridge filter:

- Dissolve 1 kg DECALCIT FILTER in 10 L of water in a bucket, insert the cartridge and let it soak overnight. Thoroughly rinse with clear water.



Find all the information about this product on our website

WARNINGS

Never mix different chemicals in their concentrated form. Avoid spilling Decalcit Filtre into the pool: when it comes into contact with chlorine, Decalcit Filtre forms chloramines. Always add the product to the water, and never the other way round

IMPORTANT RECOMMENDATIONS

Not suitable for all non acid resistant materials.