

TECHNICAL DATA SHEET

QUICKFLOCK LIQUID FLOCCULANT

Effectively fights cloudy water or translucent green water caused by metals

2 3
1 4

WATER CLARITY

ADVANTAGES

- High chemical purity
- Ideal for continuous flocculation
- For optimised filtration fineness
- Action independent of temperature

PRODUCT FUNCTION

Flocculation.

QUICKFLOCK is a liquid concentrate for continuous flocculation and removes finely dispersed, colloiddally dissolved dirt particles in swimming pools with sand filters. Ideal for use in commercial swimming pools.

PRODUCT DESCRIPTION

Liquid flocculant.

Contains: Aluminium hydroxychloride (CAS N° 12042-91-0)
Available size: 20 L

IMPORTANT RECOMMENDATIONS

Please follow the dosing pump manufacturer's instructions carefully. The filtration system must run every day (for a duration at least equal to half the water temperature). As the filtration system runs continuously, it is recommended that you backwash the filter once a week for at least 3 minutes. Please ensure you follow the dosing pump manufacturer's instructions carefully.



APPLICATION

- The ready to use QUICKFLOCK LIQUID must only be used in conjunction with automatic dosing pumps.
- The pH value must always be in the optimum range from 7.0 to 7.4.
- The dosing quantity is between 0.3 – 1.3 ml per circulated m3 of pool water, depending on the water quality. Dosing quantity according to DIN 19 643: 1.25 ml/m3.
- Due to the continuous dosing of the product, it is recommended to backwash the filter once a week for at least 3 minutes.
- Observe the manufacturers specification and operating instructions of the dosing pumps.



Find all the information about this product on our website