

TECHNICAL DATA SHEET

SUPERFLOCK® PLUS

FLOCCULANT

Effectively combats cloudy water and reduces phosphates and metals

2 3
1 4

WATER CLARITY



ADVANTAGES

- Cartridge four times thicker than the competition
- Very long-lasting effect
- Specially designed for sand/glass filters
- 3-in-1 action: clarifies, removes phosphates and metals
- Makes the water crystal-clear
- Improves filtration efficiency

PRODUCT FUNCTION

Flocculation.

Superflock® Plus is a flocculant that works continuously to combat cloudy water. Its unique formula removes metals and, thanks to the action of lanthanum it also removes the phosphates responsible for algae blooms.

PRODUCT DESCRIPTION

Solid flocculant in a flexible cartridge for sand filters

Contains: Aluminum sulfate 14 – hydrate (CAS N° 16828-12-9), Lanthanum(III) chloride hydrate (CAS N° 20211-76-1)

Available size: 1 kg

DOSING INFORMATION

Filter type: Sand / glass filter	Where: In the skimmer
Water volume: ≥10m³	When: Once per week

WARNINGS

Never mix different chemicals in their concentrated form. Always add the product to the water, never the other way round. Using Superflock® Plus results in more efficient filtration. As the filter traps more impurities, more frequent backwashing may be required. Not suitable for use with cartridge filters.

APPLICATION

- Before dosing, check the pH using BAYROL test strips or the BAYROL Pooltester, and if necessary, adjust it to the ideal range of 7.0 to 7.4.
- Place one SUPERFLOCK PLUS cartridge in the skimmer once a week, after backwashing the filter.
- For overflow pools, place the cartridge inside a bag or net and hang it in the balance tank.
- One cartridge is sufficient for up to 50 m³ of water.



Find all the information about this product on our website

IMPORTANT RECOMMENDATIONS

If the water remains cloudy despite this treatment, carry out a shock chlorination using CHLORIFIX® or CHLORYTE®. To remove copper ions, it is recommended that you temporarily raise the pH to between 7.5 and 7.8.